




The MasterRib® panel system is an exposed fastened offering that can be used for both roof and wall applications. Ideal for agricultural, light commercial, residential and storage buildings. It also works well for canopies.

Also available with DripStop, an innovative product that works by creating a medium for trapping moisture in the specially designed pockets formed within the felt's membrane. It is applied to the back of the MasterRib panel during the manufacturing process. DripStop is held to a high standard of durability and efficiency. DripStop is not susceptible to ripping, tearing or deteriorating like standard insulation and vapor barriers. Additionally, DripStop is UL 723-Approved for flame spread and smoke generation and comes with a 20-year adhesion warranty.



PRODUCT SPECIFICATIONS

Applications: Roof and Wall

Coverage Widths: 36"

Rib Spacing: 9" on center

Rib Height: 3/4"

Minimum Slope: 3:12

Panel Attachment: Exposed Fastening System

Gauges: 29 (Standard); 26 (Optional)

Finishes: Smooth (standard); Embossed (optional)

Coatings: Galvalume Plus®, Signature® 200



CATEGORY	CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
ENVIRONMENTAL	Impact Resistance	UL 2218	Determines Impact Resistance of Prepared Roof Covering Materials	Class 4 Rating
	Room Fire Performance	UL 790	Standard for Standard Test Methods for Fire Tests of Roof Coverings	See Class A Fire Rating Data Sheet
FIRE RESISTANCE	Room Fire Performance	UL 263	Standard for Standard Test Methods for Fire Tests of Roof Coverings	See Class A Fire Rating Data Sheet
STRUCTURAL	Uplift Resistance	AISI S100	Provides a standard procedure to evaluate or confirm structural performance under uniform static air pressure difference	See Section Properties and Allowable Load Table Section
	Gravity Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section
ROOF LISTINGS	Roof Performance - Underwriters Laboratories	UL 580	Determines the uplift resistance of roof assemblies consisting of the roof and roof coverings materials	Class 90 Rating - Construction Number 560
	Roof Performance - Florida Approval	UL 580 UL 1897 UL 790 ASTM E 1592	Florida product approval is the approval of products and systems, which comprise the building envelope and structural frame, for compliance with the structural requirements of the Florida Building Code.	See FL# 42379.1, 42379.2, 42382.7, 42382.8
	Roof Performance - Texas Department of Insurance	UL 580 UL 1897	TWIA provides windstorm and hail insurance in areas exposed to hurricanes and currently provides windstorm and hail coverage in the following 14 "first tier" Texas coastal counties: Aransas, Brazoria, Calhoun, Cameron, Chambers, Galveston, Jefferson, Kenedy, Kleberg, Matagorda, Nueces, Refugio, San Patricio and Willacy.	TDI 3rd Party Evaluation FL 42379.2
WALL LISTINGS	Wall Performance - Florida Approval	ASTM E1592	Florida product approval is the approval of products and systems, which comprise the building envelope and structural frame, for compliance with the structural requirements of the Florida Building Code.	See FL# 42378.7, 42378.8

Descriptions and specifications contained herein were in effect at the time this publication was approved for printing. In a continuing effort to refine and improve products, American Building Components reserves the right to discontinue products at any time or change specifications and/or designs without incurring obligation. Projects should be designed to conform to applicable building codes, regulations and accepted industry practices. To ensure you have the latest information available, please inquire or visit our website at abcmetalroofing.com.

© 2024 American Building Components, part of **Cornerstone Building Brands**, Inc. ALL RIGHTS RESERVED. 0811239991111/RevD/MS/1224