

**Conventional
Felt****Roloshield™
25 Year****Roloshield™
50 Year****Roloshield™
Lifetime**

Material	Asphalt	100% synthetic woven is the green answer to asphaltic. Manufactured from post-industrial recycled material.	100% synthetic woven with cool gray spunbond non-woven fabric surface	Premium high strength woven synthetic
Product Weight	45/60 lbs	2.0 lbs per square – 20 lbs per roll	2.0 lbs per square – 20 lbs per roll	2.8 lbs per square – 28 lbs per roll
Quantity/Size	2 squares per roll - 36" wide x 72 lineal ft	10 squares per roll – 48" wide x 250 lineal ft	10 squares per roll – 48" wide x 250 lineal ft	10 squares per roll – 48" wide x 250 lineal ft
Tear Resistance	Easy to tear	20x stronger than asphaltic felt. Highest cross directional tear resistance in the industry.	20x stronger than asphaltic felt. Highest cross directional tear resistance in the industry.	20x stronger than asphaltic felt. Highest cross directional tear resistance in the industry.
Durability	Begins to degrade immediately	UV Resistant. Can be left exposed for up to 6 months with no degrading.	UV Resistant. Can be left exposed for up to 6 months with no degrading.	UV Resistant. Can be left exposed for up to 6 months with no degrading.
Warranty	no warranty	25 year warranty	50 year warranty	Limited lifetime warranty
Part Number	N/A	ROLO25	ROLO50	ROLOL
Rolls/Pallet	N/A	48	35	35